



Product Data Sheet:

Sugar Processing and Purification: Decolourisation, Deodourisation, and Filtration

Product: RFB-SE

Carbo-UA product **RFB-SE** is an extremely high-capacity wood-activated carbon based product specifically designed for superior decolourisation, deodourisation, and filtration of sugar syrups. It is formulated for use as a high-efficiency batch-contact / body-feed media for production of premium quality sugar syrups and crystals. **RFB-SE** is especially effective in producing syrups below 50 ICUMSA in a single step, at very low solids dosage.

General Specifications

Sugar Index:	250 min (Carbo-UA Method S-11)
pH:	6.5 – 7.5 (Carbo-UA Method S-12)
Density:	0.4 - 0.6 kg/L (as packed in 20 kg bags)
Total Ash:	7% max (ASTM D2866-94)
Moisture:	28 - 35% as packed

Food Grade Certifications

Carbo-UA RFB-SE meets the requirements of the US FDA for sugar processing under certain conditions, and all applicable raw materials meet the requirements of the *Food Chemical Codex*, fourth edition.

Additional Certifications

Carbo-UA product RFB-SE is Kosher approved.

support@carboua.com

www.carboua.com

General specifications for Sugar Index and pH are based on performance on a standard sugar of Carbo-UA's selection. Customized product specifications on individual customer's feedstocks can be tailored to insure performance consistency on an individual customer basis.

Version Date: 13 December2008